



SLF WALL MOUNTED EXHAUST FANS

The SLF fan range is characterized by a very slim shape : the maximum thickness from the wall of the visible front body has been reduced to only 11 mm.

The product is therefore much less visible and fully integrated in your home environment : a perfect combination of simplicity and design together with its mirror bright surface.

The range includes 2 axial exhaust fans models with air delivery from 85 up to 300 m³/h.

It has been designed for direct duct exhausting and ventilation outdoors at air temperatures no higher than 40°C.

The electrical connection is recessed and there is a double possible cable entry : in lower or in upper position

Each model is available in **BASIC** and in **TIMER** version (timer delay adjustable between 2 and 20 minutes using a small knob installed inside the appliance)

All models are in double electrical insulation and IP 44 splash water proved. Therefore they are particularly recommended for installation in bathrooms or humid areas (following the installation safety requirements in effect in your country). All the motors are available in 230V – 50 Hz execution . In SLF 100 models, they are self protected , in SLF 150 models they are protected against overheating by a non-automatic resetting safety device.

Other ratings available upon request.

Each product complies with the EN 60335 2-80 safety standards and electromagnetic compatibility standards which are valid in EEC.

SOME SUGGESTED APPLICATIONS

Model SLF 100 : small bathrooms up to 6-8 m², small cooking corners

Model SLF 150 : Large bathrooms with showers, public bathrooms, kitchens, offices

SELECTION TABLE SLF WALL-MOUNTED EXHAUST FANS

Model	Description	Performance at 230V, 50Hz	Power at 230 V	Electric insulation	Humidity protection	Sound pressure	Q.ty carton
SLF 100	Basic version	85m ³ /h , 17 Pasc. Max	12 W	Class 2	IP 44	41 dBA	6 pcs.
SLF 100T	Timer	85m ³ /h , 17 Pasc. Max	12 W	Class 2	IP 44	41 dBA	6 pcs.
SLF 150	Basic version	300 m ³ /h, 55 Pasc. Max	30 W	Class 2	IP 44	49 dBA	6 pcs.
SLF 150T	Timer	300 m ³ /h, 55 Pasc. Max	30 W	Class 2	IP 44	49 dBA	6 pcs.

DIMENSIONS

Model	Width mm. / inch	Height mm. / inch	Maximum thickness from wall mm. / inch	Duct diameter mm. / inch	Maximum duct length mm. / inch
SLF 100	137 / 5,39	147 / 5,79	9 / 0,35	96 / 3,78	88 / 3,46
SLF 150	193 / 7,59	204 / 8,03	11 / 0,43	148 / 5,83	103 / 4

Ermete Giudici S.p.a.

Via Leonardo da Vinci, 27 • 20090 SEGRATE (MI) • ITALY

Tel. office: +39 2 2139.247/149/507

Tel. warehouse: +39 2 2135.451

Fax: +39 2 2139.732 • e-mail: giudici@giudici.com



www.ermetegiudici.com